

## Catalog Number

49302-T14

**Union, Adapter, Tee**, low pressure, 1.0 mm / 0.040 inch through hole with 10-32 to 1/4-28 reducing screw threads, Carbon PEEK Endure, round with an internal "T." Use with 1/16 inch tubing. ARE-Applied



### Additional Info

This carbon-PEEK, Endure™ brand adapter is used to connect three pieces of low pressure, 1/16th OD tubing with 1.0mm / 0.040 inch ID.

- Maximum Temperature: 100°C
- Maximum Pressure: 1,000 psig.
- Click [HERE](#) for economical pack of 10.

This Tee (T) union through hole has two internal 90° turns (connections). With this you can "blend the flow" of two lines or "split the flow" into two outward lines of liquid, depending on which flow direction you use.

*NOTE: This union requires two low pressure 10-32 threaded male nuts and matching flangeless ferrules and one 1/4-28 threaded male nut with matching flangeless ferrule. Nuts and ferrules are sold separately.*

### MicroSolv Technology Corporation

9158 Industrial Blvd. NE, Leland, NC 28451

tel. (732) 380-8900, fax (910) 769-9435

Email: [customers@mtc-usa.com](mailto:customers@mtc-usa.com)

Website: [www.mtc-usa.com](http://www.mtc-usa.com)

Printed On 2024/05/19