

## Catalog Number

47451-W-41-005

**Adapter**, for use with low to medium pressure HPLC. Waters female to 1/4-28 male connection, 0.40 mm / 0.016 bore size. PEEK. ARE-Applied Research brand. 5/PK.



### Additional Info

This finger tightened adapter makes changing from Waters® male nuts to 1/4-28, non-Waters standard connections very convenient especially when using Waters style fittings. This all-PEEK adapter has a Waters style female, screw threaded port on one side and a 1/4-28 screw threaded, male connector on the other side. Click [HERE](#) for the differences between Waters and standard connections.

- Maximum Temperature: 100°C
- Maximum Pressure: 8,000 psig.
- Click [HERE](#) for economical pack of 10.
- Click [HERE](#) for more Waters adapters to standard 10-32 connections.
- 

The "flat" section on the knurled adapter allows for using a wrench for an extra 1/8 of clockwise turn for tighter sealing or a slight counterclockwise turn to help remove if a tight fitting is too hard

### MicroSolv Technology Corporation

9158 Industrial Blvd. NE, Leland, NC 28451

tel. (732) 380-8900, fax (910) 769-9435

Email: [customers@mtc-usa.com](mailto:customers@mtc-usa.com)

Website: [www.mtc-usa.com](http://www.mtc-usa.com)

### Price

**\$313.46**

Printed On 2024/05/19